

Metal Washers

Model: SD-W

Designed for the suspension of non-insulated stationary pipe lines. The insert nut allows a vertical adjustment after installation is tapped to NFPA reduced rod size standards. SD-HB has a layer of felt which separate the pipe from the hanger to reduce vibration and sound.



Product Specifications:

Available Size	1.7mm - 39mm
Material	Carbon Steel, Alloy Steel
Standards	DIN125
Application	Water, HVAC & Fire-Fighting
Coating Finish	Electro-Galvanized as per ASTM B633 Standards

Metal Washers

Product Dimensions:

Nominal Washers mm	Nominal Thread mm	Inside Diameter (d) mm		Outside Diameter (d) mm		Thickness mm		
		Min.	Max.	Min.	Max.	Nominal	Min.	Max.
1.7	1.6	1.7	1.84	3.7	4	0.3	0.25	0.35
1.8	1.7	1.8	1.94	4.2	4.5	0.3	0.25	0.35
2.2	2	2.2	2.34	4.7	5	0.3	0.25	0.35
2.5	2.3	2.5	2.64	5.7	6	0.5	0.45	0.55
2.7	2.5	2.7	2.84	5.7	6	0.5	0.45	0.55
2.8	2.6	2.8	2.94	6.64	7	0.5	0.45	0.55
3.2	3	3.2	3.38	6.64	7	0.5	0.45	0.55
3.7	3.5	3.7	3.88	7.64	8	0.5	0.45	0.55
4.3	4	4.3	4.48	8.64	9	0.8	0.7	0.9
5.3	5	5.3	5.48	9.64	10	1	0.9	1.1
6.4	6	6.4	6.62	11.57	12	1.6	1.4	1.8
7.4	7	7.4	7.62	13.57	14	1.6	1.4	1.8
8.4	8	8.4	8.62	15.57	16	1.6	1.4	1.8
10.5	10	10.5	10.77	19.48	20	2	1.8	2.2
13	12	13	13.27	23.48	24	2.5	2.3	2.7
15	14	15	15.27	27.48	28	2.5	2.3	2.7
17	16	17	17.27	29.48	30	3	2.7	3.3
19	18	19	19.33	33.38	34	3	2.7	3.3
21	20	21	21.33	36.38	37	3	2.7	3.3
23	22	23	23.33	38.38	39	3	2.7	3.3
25	24	25	25.33	43.38	44	4	3.7	4.3
27	26	27	27.33	49.38	50	4	3.7	4.3
28	27	28	28.33	49.38	50	4	3.7	4.3
29	28	29	29.33	49.38	50	4	3.7	4.3
31	30	31	31.39	55.26	56	4	3.7	4.3
33	32	33	33.62	58.8	60	5	4.4	5.6
34	33	34	34.62	58.8	60	5	4.4	5.6
36	35	36	36.62	64.8	66	5	4.4	5.6
37	36	37	37.62	64.8	66	5	4.4	5.6
39	38	39	39.62	70.8	72	6	5.4	6.6

- Note:
- Measurements are subject to 5% tolerance.
 - Other Sizes available on request.
 - Hot Dipped Galvanized can be supplied upon request.

Metal Washers

Miscellaneous Data:

1. Ordering Information

Example: SD-W-1-15

- SD-W is the part number
- (1) Electro-Galvanized Coating
- (15) Size

2. Contact Information

For further information on any aspect of the SHIELD Pipe Supports please contact below:

MIDDLE EAST & AFRICA	UNITED KINGDOM
Jebel Ali Free Zone, Dubai, UAE P.O Box: 61199 Tel.: +971 4 881 2070 Fax: +971 4 881 2198 Email: shieldme@shielglobal.com	Unit 3, Endeavor Drive, Basildon-Essex, SS3 14WF Tel.: +44 1708 377731 Fax: +44 1708347637 Email: shielduk@shielglobal.com