

# VIZM.EX6660 - Fittings, Rubber Gasketed

## Fittings, Rubber Gasketed

### SHIELD FIRE SAFETY & SECURITY LTD

Unit 3, Endeavour Dr  
Basildon, SS14 3WF United Kingdom

EX6660

### Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
SDG-24	Rolled, Cut	4200 E	1-1/4, 1-1/2, 2	500
SDG-24	Rolled, Cut	4200 E	3, 4	300
SDG-24	Rolled, Cut	4200 E	76.1mm	300
SDG-24	Rolled, Cut	4200 D	139.7mm	300
SDG-24	Rolled, Cut	1387-M	165.1mm	300
SDG-24	Rolled, Cut	3454-20	216.3mm	300
SDG-24	Rolled	10	2-1/2	500
SDG-24	Rolled	10	6, 8, 10	300
SDG-24	Rolled, Cut	40	2-1/2	500
SDG-24	Rolled, Cut	40	6, 8, 10	300
SDG-24	Rolled	10	6, 8, 10	300
SDG-24	Rolled, Cut	40	2-1/2	500
SDG-24	Rolled, Cut	40	6, 8, 10	300
SDGL 22V	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
SDGL 22V	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
SDGL 22V	Rolled	T3091- 1993	6-1/2 OD	300
SDGL 22V	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
SDGL 22V	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
SDGL 26	Rolled	5	2	300

SDGL 26	Rolled	10	2, 2-1/2, 3	300
SDGL 26	Rolled	10	4, 5, 6	300
SDGL 26	Rolled, Cut	40	2, 2-1/2, 3	500
SDGL 26	Rolled, Cut	40	4, 5, 6	300
SDGL 26	Rolled	GB/T 3091	2, 2-1/2, 3	300
SDGL 26	Rolled	GB/T 3091	4, 6-1/2OD	300
SDGL 26	Rolled	WGalweld 7	2, 2-1/2, 3, 4	300
SDGL 26	Rolled, Cut	GB/T 17395	5-1/2OD/4.5mm	300
SDGL 26	Rolled, Cut	GB/T 17395	3OD/4mm	400
SDGL 26	Rolled	GB/T 21835	6/4.5mm	300
SDGL 24	Rolled	5	1-1/4, 1-1/2, 2	300
SDGL 24	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500
SDGL 24	Rolled	10	5, 6, 8, 10	300
SDGL 24	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	400
SDGL 24	Rolled, Cut	40	5, 6, 8, 10, 12	300
SDGL 24	Rolled	GB/T 3091	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	400
SDGL 24	Rolled	GB/T 3091	5-1/2OD, 6-1/2OD, 8	300
SDGL 24	Rolled	WGalweld 7	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
SDGL 24	Rolled, Cut	GB/T 17395	3OD/4mm, 4-1/4OD/4mm, 5-1/2OD/4.5mm, 6-1/4OD/5mm	300
SDGL 24	Rolled, Cut	JIS G3452	216.3mm, 267.4mm	300
SDGL 24	Rolled	GB/T 21835	6/4.5mm, 10/6.3mm, 12/7.1mm	300
SDG 20	Rolled	10	4	365

SDG 20	Rolled	10	3, 6, 8, 10	300
SDG 20	Rolled	40	3, 4, 6, 8, 10	300
SDG 20	Rolled	1387-M	3 OD, 5-1/2 OD, 6-1/2 OD	300
SDG 20	Rolled	1387-H	3 OD, 5-1/2 OD, 6-1/2 OD	300
SDG 20	Rolled, Cut	4200	108.0 / 4.0mm, 141.3 / 6.3mm, 159.0 / 4.0mm	300
SDG 20	Rolled, Cut	3454-20	216.3 / 6.4mm	300
SDG 28	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	750
SDG 28	Rolled, cut	40	2, 2-1/2, 3, 4, 5, 6, 8	750
SDG 28	Rolled, cut	T21835	3OD(5.0mm), 5-1/2OD (6.3mm), 6-1/2OD(7.1mm)	750
SDG 28	Rolled	10	10, 12	500
SDG 28	Rolled, cut	40	10, 12	500

**Flexible coupling**

<b>Model</b>	<b>Groove Type</b>	<b>Pipe</b>	<b>Size (in.)</b>	<b>Rated Pressure (psig)</b>
SDGL 25V	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
SDGL 25V	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
SDGL 25V	Rolled	T3091-1993	6-1/2 OD	300
SDGL 25V	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
SDGL 25V	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
SDGL 27	Rolled	10	2, 3, 4, 6	500
SDGL 27	Rolled	10	8	400
SDGL 27	Cut	40	2, 3, 4, 6	500
SDGL 27	Cut	40	8, 10, 12	400
SDG 30	Rolled	10	2, 2-1/2, 3, 4, 5	300
SDG 30	Rolled	10	1-1/4, 1-1/2, 6, 8	500
SDG 30	Rolled	1387-10	3 OD, 6-1/2 OD	300
SDG 30	Rolled	1387-M	5-1/2 OD	450
SDG 30	Rolled	1387-M, 10	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
SDG 30	Rolled	EN10255-M	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360

SDG 30	Rolled, Cut	40	2, 2-1/2, 3, 4, 5	300
SDG 30	Rolled, Cut	40	1-1/4, 1-1/2, 6, 8	500
SDG 30	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
SDG 30	Rolled, Cut	1387-H	5-1/2 OD	450
SDG 30	Rolled, Cut	1387-H, 40	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
SDG 30	Rolled	EN10255-H	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360
SDG 30	Rolled, cut	10, 40	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3; 5 x 4; 6 x 4, 5; 8 x 6	360
SDG 30	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
SDG 30	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
SDG 30	Rolled, Cut	4200	73.0 / 3.2 x 33.7 / 3.2mm; 76.1 / 3.6 x 33.7 / 3.2mm; 88.9 / 3.2 x 33.7 / 3.2mm; 114.3 / 3.6 x 33.7 / 3.2mm; 168.3 / 4.0 x 88.9 / 3.2mm	300
SDG 30	Rolled, cut	4200	60.3mm(4.0mm) x 33.7(3.2mm), 48.3mm(4.0mm); 219.1mm(5.0mm) x 168.3mm(5.0mm)	360
SDG 30	Rolled, Cut	4200	273.0 / 6.3mm, 323.9 / 6.3mm	500
SDG 30	Rolled, Cut	10, 40	6 x 6-1/2OD(6.3mm)	300
SDG 30	Rolled	GB/T 21835	6-1/2OD(6.3mm) x 3;	300
SDG 30	Rolled, Cut	GB/T 21835	3OD(4.5mm) x 2-1/2(4.5mm)	300
SDG 27	Rolled, Cut	4200	60.3 / 3.2mm, 73.0 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm, 114.3 / 3.6mm, 141.3 / 6.3mm	750
SDG 27	Rolled, Cut	4200	168.3 / 4.0mm, 219.1 / 5.0mm	750
SDG 27	Rolled, Cut	EN10255-M	139.7mm, 165.1 / 5.0mm	750
SDG 27	Rolled	10	12	500
SDG 27	Rolled, Cut	40	12	500
SDG 27	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	750

SDG 27	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	750
--------	-------------	----	-------------------------	-----

**Reducing Coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
SDGL 30	Rolled	T3091	2x1-1/2, 3 ODx1-1/2, 3 ODx2, 3x1-1/2, 3x2, 3x3 OD, 4x1-1/2, 4x2, 4x3 OD, 4x3, 6x3, 6x4, 8 / 6 mm x6	300
SDGL 30	Rolled	T17395xT3091	2-1/2 / 4 mm x1-1/2, 2-1/2 / 4 mm x2	300
SDGL 30	Rolled	T3091xT17395	3x2-1/2 / 4 mm, 4x2-1/2 / 4 mm	300

**Side outlet**

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (psig)
SDG 49	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2, 3; 5 x 1-1/4, 1-1/2, 2, 2-1/2, 3; 6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
SDG 49	Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2; 5-1/2 OD x 2, 2-1/2, 3; 6-1/2 OD x 2, 2-1/2, 3	300
SDG 47	Threaded	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2, 3; 5 x 1-1/4, 1-1/2, 2, 2-1/2, 3; 6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
SDG 47	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2; 5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3; 6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	300
SDGL 44	Rolled	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2	300
SDGL 44	Rolled	T3091	5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
SDGL 44	Grooved	10, 40	2-1/2 x 1; 4 x 2-1/2, 3OD, 3	300
SDGL 44	Grooved	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3; 6-1/2OD x 4	300

SDGL 42	Threaded	T3091	1-1/2x1, 3 ODx2, 5x1, 5x1-1/4, 5x1-1/2, 5x2	232
SDGL 42	Threaded	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2, 5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
SDGL 42	Threaded	10, 40	2-1/2 x 1-1/4; 4 x 2-1/2, 3OD, 3	300
SDGL 42	Threaded	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3	300
SDGL 40	Threaded	T3091	1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 2x1/2, 2x3/4, 2x1, 3 ODx1/2, 3 ODx3/4, 3 ODx1	300
SDGL 40	Threaded	T17395	2-1/2 / 4 mm x1/2, 2-1/2 / 4 mm x3/4, 2-1/2 / 4 mm x1	300
SDGL 44V	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2; 8 x 2, 2-1/2	300
SDGL 42V	Threaded	10, 40	2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1, 1-1/4, 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2	300
SDG 44	Grooved	10, 40	3 x 2;	300
			4 x 2, 3OD;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 2, 3OD;	
			10 x 3OD, 3	
SDG 44	Grooved	1387- M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	
SDG 44	Grooved	10, 40	3 x 1;	300
			4 x 1;	
			8 x 76.1mm, 3, 108.0mm, 4	
SDG 44	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2; 4 x 1-1/4, 1-1/2, 2-1/2, 3; 6 x 1-1/2, 2-1/2, 3, 4; 8 x 2, 2-1/2	400
SDG 44	Grooved	4200	76.1 / 3.6 x 33.7 / 3.2mm;	300
			133.0 / 3.2mm x 88.9mm;	

			139.7 / 3.6mm x 42.4mm, 48.3mm;	
			273.0 / 6.3 x 108.0 / 4.0mm, 114.3 / 3.6mm	
SDG 44	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	
SDG 44	Grooved	1387-M	165.1 x 114.3mm	225
SDG 44	Grooved	GB/T 21835	6-1/4OD(6.3mm) x 2	300
SDG 44	Grooved	10, 40	3 x 1, 1-1/4, 1-1/2, 2;	300
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			5 x 2;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 2, 2-1/2, 76.1mm, 3, 108.0mm, 4	
SDG 44	Grooved	10, 40	6 x 4	225
SDG 44	Grooved	10, 40	5 x 2-1/2, 3	400
SDG 44	Grooved	4200	133.0 / 3.2mm x 88.9mm;	300
			139.7 / 3.6mm x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
SDG 44	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	
SDG 44	Grooved	1387-M	165.1 x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
SDG 44	Grooved	1387-M	165.1 x 108.0mm, 114.3mm	225
SDG 44	Grooved	GB/T 21835	6-1/4OD(6.3mm) x 3	300
SDG 42	Threaded	10, 40	1 x 1/2;	300
			1-1/4 x 1/2, 3/4;	
			1-1/2 x 1/2, 3/4	
			3 x 2;	
			4 x 2;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 2, 3	

SDG 42	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2;	300
			5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	
SDG 42	Threaded	10, 40	8 x 1, 1-1/4, 1-1/2, 2-1/2, 76.1mm, 3, 4	300
SDG 42	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2; 2-1/2 x 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2-1/2, 3; 6 x 1-1/2, 2-1/2, 4; 8 x 2	400
SDG 42	Threaded	4200	273.0 / 6.3 x 114.3 / 3.6mm	225
SDG 42	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
SDG 42	Threaded	4200	76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm;	300
			108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			273.0 x 48.3 / 4.0mm, 60.3 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm	
SDG 42	Threaded	4200	60.3mm(3.2mm) x 21.3mm(2.8mm), 26.9mm(2.9mm); 73.0mm(3.2mm) x 21.3mm(2.8mm), 26.9mm(2.9mm);	400
SDG 42	Threaded	1387-M	165.1 x 21.3mm, 26.9mm	300
SDG 42	Threaded	1387-M	165.1 x 114.3mm	225
SDG 42	Threaded	10, 40	3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	300
			4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			5 x 2;	
			6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3, 4	
SDG 42	Threaded	10, 40	6 x 4	225



SDG 42	Threaded	4200	108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	300
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
SDG 42	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
SDG 42	Threaded	1387-M	165.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
SDG 42	Threaded	1387-M	165.1 x 114.3mm	225
SDG 42	Threaded	10, 40	5 x 1-1/2	400
SDG 48	Threaded and Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
SDG 48	Threaded and Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	

**Flange adapter**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
SDGL 15B	Rolled	T3091	2, 3 OD, 3, 4, 5-1/2 OD, 6, 8 / 6 mm	300
SDGL 15B	Rolled	T3091-1993	6-1/2 OD	300
SDGL 15B	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm, 5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 / 6 mm	300
SDGL 15D	Rolled	10, 40	2, 2-1/2, 3, 4, 5, 6, 8	300
SDGL 15D	Rolled	10, 40	10	175

SDG 15C	Rolled, Cut	1387-M	165.1mm	225
SDG 15E	Rolled	10	2, 3, 4, 8	300
SDG 15E	Rolled, Cut	40	2, 3, 4, 8	300
SDG 15E	Rolled	GB/T 21835	6-1/2OD(6.3mm)	300

**Side outlet**

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (psig)
SDG 40	Threaded	4200	42.4 / 3.6 x 21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm; 48.3 / 4.0 x 21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm; 60.3 / 3.2 x 21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm; 73.0 / 3.2 x 21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm; 76.1 / 3.6 x 21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm; 88.9 / 3.2 x 33.7 / 3.2 mm	300
SDG 18	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 18	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 18	Rolled, Cut	T21835	3OD(4.5mm), 5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300
SDG 18	Rolled, Cut	3454-40	216.3mm	300
SDG 18	Rolled, Cut	3452-SGP	216.3mm	300
SDG 18	Rolled, Cut	EN 10255-H	76.1mm(4.5mm), 139.7mm(5.4mm), 165.1mm(5.4mm)	300
SDG 19	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 19	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 19	Rolled, Cut	T21835	3OD(4.5mm), 5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300
SDG 19	Rolled, Cut	3454-40	216.3mm	300
SDG 19	Rolled, Cut	3452-SGP	216.3mm	300
SDG 19	Rolled, Cut	EN 10255-H	76.1mm(4.5mm), 139.7mm(5.4mm), 165.1mm(5.4mm)	300

**Coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
SDG 22	Rolled	10	1-1/4, 1-1/2, 2-1/2	500
SDG 22	Rolled	10	2, 3, 4, 5, 6	500
SDG 22	Rolled	10	8	500

SDG 22	Rolled	10	10, 12	500
SDG 22	Rolled	1387-10	3 OD, 6-1/2 OD	300
SDG 22	Rolled	1387-M	5-1/2 OD	450
SDG 22	Rolled, Cut	40	1-1/4, 1-1/2	500
SDG 22	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6	500
SDG 22	Rolled, Cut	40	8	500
SDG 22	Rolled, Cut	40	10, 12	500
SDG 22	Rolled	ASME B36.10M-10	14, 16, 18, 20, 24	300
SDG 22	Rolled, Cut	ASME B36.10M-40	14, 16, 18, 20, 24	300
SDG 22	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
SDG 22	Rolled, Cut	1387-H	5-1/2 OD	450
SDG 22	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
SDG 22	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
SDG 22	Rolled, Cut	3454-20	267.4 / 6.4mm, 318.5 / 6.4mm	225
SDG 22	Rolled, Cut	4200	355.6 / 6.3mm, 406.4 / 6.3mm	175

**Flexible coupling**

<b>Model</b>	<b>Groove Type</b>	<b>Pipe</b>	<b>Size (in.)</b>	<b>Rated Pressure (psig)</b>
SDG 25	Rolled	10	2, 2-1/2, 3, 4, 5	300
SDG 25	Rolled	10	1-1/4, 1-1/2, 6, 8	500
SDG 25	Rolled	1387-10	3 OD, 6-1/2 OD	300
SDG 25	Rolled	1387-M	5-1/2 OD	450
SDG 25	Rolled	1387-M, 10	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
SDG 25	Rolled	EN10255-M	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360

SDG 25	Rolled, Cut	40	2, 2-1/2, 3, 4, 5	300
SDG 25	Rolled, Cut	40	1-1/4, 1-1/2, 6, 8	500
SDG 25	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
SDG 25	Rolled	ASME B36.10M-10	14, 16, 18, 20, 24	300
SDG 25	Rolled, Cut	ASME B36.10M-40	14, 16, 18, 20, 24	300
SDG 25	Rolled, Cut	1387-H	5-1/2 OD	450
SDG 25	Rolled, Cut	1387-H, 40	3 OD x 1-1/2, 2; 3 x 3 OD; 4 x 3 OD; 8 x 6-1/2 OD	300
SDG 25	Rolled	EN10255-H	88.9mm x 60.3mm; 114.3mm x 60.3mm, 88.9mm; 165.1mm x 114.3mm;	360
SDG 25	Rolled	10	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3; 5 x 4; 6 x 4, 5; 8 x 6	360
SDG 25	Rolled, cut	40	2-1/2 x 2; 3 x 2, 2-1/2; 4 x 2, 2-1/2, 3; 5 x 4; 6 x 4, 5; 8 x 6	360
SDG 25	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
SDG 25	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
SDG 25	Rolled, Cut	4200	73.0 / 3.2 x 33.7 / 3.2mm; 76.1 / 3.6 x 33.7 / 3.2mm; 88.9 / 3.2 x 33.7 / 3.2mm; 114.3 / 3.6 x 33.7 / 3.2mm; 168.3 / 4.0 x 88.9 / 3.2mm	300
SDG 25	Rolled, cut	4200	60.3mm(4.0mm) x 33.7(3.2mm), 48.3mm(4.0mm); 219.1mm(5.0mm) x 168.3mm(5.0mm)	360
SDG 25	Rolled, Cut	4200	273.0 / 6.3mm, 323.9 / 6.3mm	500
SDG 23	Rolled	10	2, 3, 4, 6, 10	300
SDG 23	Rolled Cut	40	2, 3, 4, 6, 10	300
SDG 23	Rolled Cut	GB/T 21835	5-1/2OD(5.6mm), 6-1/2OD(6.3mm)	300

SDG 23	Rolled	10	6 x 4	300
SDG 23	Rolled Cut	40	6 x 4	300
SDG 23	Rolled	ASME B36.10M-10	16	300
SDG 23	Rolled, Cut	ASME B36.10M-40	16	300
SDG 23	Rolled, cut	EN 10255 H	76.1mm(4.5mm)	300

**Flange adapter**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
SDG 15	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 15	Rolled	1387-10	3OD, 6-1/2 OD	300
SDG 15	Rolled	10	10, 12	225
SDG 15	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	300
SDG 15	Rolled, Cut	1387-40	3OD, 6-1/2 OD	300
SDG 15	Rolled, Cut	40	10, 12	225
SDG 15	Rolled, Cut	4200	48.3 / 4.0mm, 108.0 / 3.6mm	300
SDG 15	Rolled, Cut	4200	133.0 / 3.2mm, 139.7 / 3.6mm, 159.0 / 4.5mm	225
SDG 15	Rolled	ASME B36.10M-10	14	300
SDG 15	Rolled, Cut	ASME B36.10M-40	14	300
SDG 15D	Rolled	10	2, 2-1/2, 3, 4	300
SDG 15D	Rolled	10	5	250
SDG 15D	Rolled, cut	40	5	250
SDG 15D	Rolled	ASME B36.10M-10	14	300
SDG 15D	Rolled, Cut	ASME B36.10M-40	14	300
SDG 15D	Rolled, Cut	4200	219.1 / 5.0mm, 273.0 / 6.3mm, 323.9 / 6.3mm	250

The fittings are suitable for use in dry pipe systems for temperatures to -40 F with the exception of Model SDG-24, SDG 15E

Model SDG 40, SDG 42 in the 1/2 in. and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models SDG 42, SDG 44, SDG 48, SDG 40, SDGL 44, SDGL 42, SDGL 40, SDGL 44V and SDGL 42V in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Models SDG 42, SDGL 42 with 2 in. and larger main run size and 1 in. nominal outlets are intended for direct connection to sprinklers.

Models SDGL40 and SDGL 42V in the 1/2, 3/4, 1 in. nominal outlets are intended for direct connection to sprinklers.

Suitable for use in dry pipe systems for temperatures to -40 F

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

1387-10 refers to BS 1387 Schedule 10 steel pipe

1387-40 refers to BS 1387 Schedule 40 steel pipe

1387-10 refers to BS 1387 Schedule 10 steel pipe

1387-40 refers to BS 1387 Schedule 40 steel pipe

T3091 refers to GB/T3091-2001 ordinary steel pipe

T3091-1993 refers to GB/T3091-1993 ordinary steel pipe

GB/T 3091 refers to GB/T3091 ordinary steel pipe

T17395 refers to GB/T17395-1998 steel ordinary pipe

GB/T 17395 refers to GB/T 17395 steel ordinary pipe

GB/T 21835 refers to GB/T 21835 ordinary steel pipe

6-1/2 OD pipe is GB/T3091-1993 pipe, 2-1/2", 4-1/4 OD, 5-1/4 OD, 5" and 6-1/4 OD pipes are GB/T17395-1998 pipes, the rest pipes are GB/T3091-2001 pipes

5 refers to ASME B36.10-2004 ordinary steel pipe

WGalweld 7 refers to Wuppermann Stahl GmbH, model WGalweld 7 (Galvanized) pipe, file number EX16421

JIS G3452 refers to JIS G3452-2014 ordinary steel pipe

Trademark and/or Tradename: "SD",  ,  , 

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."